

FLG 190A-GREEN

Outstanding laser line visibility

 green laser



TECHNICAL DATA		FEATURES	SUPPLIED WITH FL 190A GREEN (LC 2) + FR 45	
			ART.-NO. 292195	
Self-levelling range	± 3°	<ul style="list-style-type: none"> · Instant self-levelling · Horizontal fully automatic self-levelling rotating laser · Vertical levelling using adjustment screw · Variable rotating speed · Permanent 90° beam to zenith · Rechargeable NiMH batteries with intelligent charger · Integrated floor / wall mount with adjustment screw 	<ul style="list-style-type: none"> · Receiver FR 45 with clamp for levelling staff · NiMH batteries · Charger · Carrying case 	
Accuracy	± 1,5 mm / 10 m			
Working range without receiver Ø	40 m*			
Working range with receiver Ø	600 m			
Rotating speed (rpm)	200, 400, 600			
Power supply	NiMH			
Operating time	10 h			
Dust / water protection	IP 54			
Laser diode / class	635 nm / 2			
Temperature range	-10°C to +45°C			
Weight (instrument with battery)	1,5 kg			
* depending on the room illumination				

SUPPLIED WITH FL 190A GREEN (LC 2) + FR-DIST 30	
ART.-NO. 292198	
<ul style="list-style-type: none"> · Receiver FR-DIST 30 with clamp for levelling staff · NiMH batteries · Charger · Carrying case 	