

PN | Optical levels

PNAL | Optical levels (SKU no. 205-PNAL-24 and 205-PNAL-32)

Features

- Sturdy metal housing with rubber reinforcement
- Water and dust protected
- Fast aperture
- Magnetically dampened compensator
- Circular vial with penta prism
- Fine motion knobs on both sides with friction-braked rotation, endless horizontal drive
- Large focusing knob
- Target collimator
- Transportation case with double lock and accessories
- 2 years of warranty



Technical data

Magnification	24x	32x
Accuracy at 1 km double leveling	2 mm	1 mm
Objective aperture	36 mm	40 mm
Field of view	1° 20'	1° 20'
Minimum focus range	0.3 m	0.3 m
Graduated circle	1°/1 gon	1°/1 gon
Thread	5/8"	5/8"
Weight without case	1.8 kg	1.8 kg

Application

For building patios, houses and baseplates, for landscaping, excavation height control, survey work on the jobsite and in the field

Scope of delivery

- Optical level
- Transportation case
- Protective cap
- Plumb
- Cord
- Adjustment tool
- Allen wrench key
- Instruction manual

Service

Our technicians calibrate, service and repair your optical levels. We offer a base and full service according to the customer's wish. Contact us for more information!



Offer your customers a leveling set with tripod and rod. Ask for your best set price!